

Botron High Quality Toe grounders are made from the best products on the market. Our grounders have the largest cup design with better floor contact and better testing when soiled. With its dual layer construction non-marking interior and conductive outer surface is designed for long wear. The 10" conductive ribbon provides a safe static discharge to ground when tucked into your shoe. Adjustable at the toe area for comfort. We sew our own products so we can make it any way you need. The **B7522** has stretch Velcro fastening system with a built in 1-megohm resistor, we also offer 2meg and no resistor products. **Disclaimer.** All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user. The statements herein shall have no force or effect.



PROPERTIES

SPECIFICATIONS

Sole Interior:	Non-Marking
Sole Exterior:	<10 ^s
Material:	Two layer rubber
Ribbon:	conductive 10"
Cup Design:	Full Coverage Heel & Toe
Charge Decay:	<0.01Sec
Thickness:	0.08-0.13mm
RTG: with 1meg	<2x10 ⁶ -1x10 ⁷
Meets:	ANSI/ESD S.20.20 & Mil 263
3/4" Stretch Velcro:	Fastening system
Packing:	1 per.bag / bags of 10
Sizes:	One size fit all

OTHER PRODUCTS:

- B7500** Ergo-One heel grounder
- B7571** Non-Marking heel grounder
- B7525** Snap-Loc heel grounder
- B7591** Red Hi-Visibility heel grounder
- B7525** Non-Marking Toe grounder
- Many other heel & toe grounders

Per ANSI S20.20 protective flooring used with approved footwear may be used as an alternative to wrist straps. It is always best to use wrist straps at the workstation. Botron manufactures 17 types of heel and toe grounders to safely remove static charges from mobile workers.

RELATED TEST EQUIPMENT:

- B82250** Dual Tester with stand
- B82450** Combo tester with stand
- B8525** Deluxe Dual tester & stand
- B85502** Calibration unit for testers
- B8506** Wall test station

Lean Stream, LLC
 2153 O'Toole Avenue, Suite G
 San Jose, CA, 95131
 Phone: **408-894-9400**
 Fax: 408-954-9989
 Email: info@lean-stream.com / www.lean-stream.com

TOE GROUNDERS