


Botron Type EM Conductive Sponge rubber mats and runners designed to reduce strain from standing on hard surfaces. Slip and soil resistant. 5/8" thick with beveled edges and comes with grounding hardware on all cut mats. Per. ANSI/ESD and EIA-625 ESD standards. All cut mats should be grounded with a **B9701** floor mat ground. **Disclaimer.** All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user. The statements herein shall have no force or effect.

Energy-Absorbing 5/8" conductive rubber



5/8" Beveled



B9701
Floor mat grd

PROPERTIES

SPECIFICATIONS

Material:	Sponge rubber
Thickness:	5/8" +/-
RTG:	$2 \times 10^5 - x < 10^6$
RTT:	$3 \times 10^5 - x < 10^6$
Charge Decay:	<0.01Sec
Texture:	Slightly textured
Color:	Black
Sizes:	22" x 3', 3' x 5', 3' X 20'
Testing:	100volts @ 50% relative humidity
Edges:	Beveled

Warranty: This mat is guaranteed against defects

in materials and workmanship for two years.

Chemical resistance: Excellent, will not be affected by petroleum products and chemicals.

BEM223	22" X 3' mat w/grd
BEM35	3'x5' mat w/grd
BEM320	3' x20' roll

OTHER PRODUCTS:

B54260	2'x 60' Type O roll
B543060	30"x 60' Type O roll
B54360	3'x 60' Type O roll

Test Equipment:

B8571	Digital & Analog Surface tester
B8563	Analog Surface tester
BSRM-10	10 Light surface tester
BSRM-6	6 Light surface tester
B8560	New 10 light surface tester

RELATED PRODUCTS:

B4023	2'x3' Diamond anti-fatigue
B4035	3'x5' Diamond anti-fatigue
B40325	3'x25' Diamond anti-fatigue
B40375	3'x75' Diamond anti-fatigue

Lean Stream, LLC
2153 O'Toole Avenue, Suite G
San Jose, CA, 95131
Phone: 408-894-9400
Fax: 408-954-9989
Email: info@lean-stream.com / www.lean-stream.com

TYPE EM, ERGONOMIC SPONGE RUBBER MAT